

Rust Stop 150 - D

Oil/wax based anti-rust product

Thin, clear, highly penetrating oil/wax based anti-rust product with effective rust inhibitors added. Rust stop150-d has great absorption and moisture displacing properties.

Range of application:

Suitable for all surfaces requiring rust protection. Can be used as a primer before applying SUVO 216. Ideal for steel components and for safeguarding machined steel parts in production lines. Provides corrosion protection during storage and transport. Also suitable for protecting interior components such as gearbox and transmission parts.

Instructions for use:

The surfaces must be clean, dry, and free from dirt before application. Avoid applying at temperatures below 10°C. Shake or stir the

product thoroughly before use. Apply using a high-quality brush or roller suitable for oil-based products, or with an air-mix or airless spray gun.

Package

01-1050 / 500-ml spray (12 pcs / pack)
01-340 / 1-lit can
01-335 / 5-lit can
01-330 / 10-lit can
01-325 / 25-lit can
01-320 / 60-lit drum
01-300 / 208-lit drum

Technical data	
Color:	Clear
Consistency:	Thin liquid
Type of film:	Oil, Vaxy
Dry content:	20 – 30%
Volatiles solvents:	70 – 80%
Film thickness:	8 – 10 µm
Application temperature:	>10° C
Removal with:	Clairsolrens, Clearrens or LHG Rensevæske
Drying time:	Approximately 12 hours depending on layer thickness and temperature.
Storing temperature:	5 – 40° C

For further information we recommend the safety data sheet or instruction on package.