

SUVO Non Nafta

Solventfree anti-corrosion wax

SUVO Non Nafta is a rust preventive product free from solvents. Low viscosity binding compounds and additives have been mixed to enable application at room temperature. The material forms a soft waxy, strongly hydrofob corrosive protecting film.

Range of application

SUVO Non Nafta is a thin, penetrating rust protective compound intended for treatment of the hollow spaces of motor vehicles according to the ML method. In addition, it may also be used as transport and storage protection for machines, machine parts, beams, motor parts etc.

Package

01-1043 / 500-ml spray (12 pcs / pack)
01-404 / 5-lit can
01-403 / 10-lit can
01-402 / 25-lit can
01-401 / 60-lit drum
01-400 / 208-lit drum

Instructions for use

We recommend applying SUVO Non Nafta with high- or low pressure spraying according to the ML method for hollow spaces. Other details may be sprayed, brushed or dipped.

Technical data	
Color:	Light brown
Consistency:	Liquid
Type of film:	Soft, Vaxy
Density at 20°:	930 ± 30 kg/m ³
Dry content:	> 97 %
Volatiles solvents:	< 1%
Film thickness:	40 – 60 µm
Application temperature:	15 – 35° C
Removal with:	Clairsolrens, Clearrens or LHG Rensevæske
Storing time:	24 months
Storing temperature:	5 – 35° C

For further information we recommend the safety data sheet or instruction on package.